



## ROCKSLATE 600X900X20mm

### Technical Specifications Physical properties

	Test of Norm	Value of Norm	N&C Value
Slip Resistance (UK Pendulum Test Values Rating)	Slider 96 Slider 55		Slider 96 = PTV36 <sup>+</sup>
Water Absorption (%)	ISO 10545-3		<0.5%
Breaking Strength	ISO 10545-4		>2500N/mm <sup>2</sup>
Modulus of Rupture	ISO 10545-4		>40N/mm <sup>2</sup>
Resistance to Surface Abrasion	ISO 10545-7		PEI 3 & 4
Deep Abrasion Resistance	ISO 10545-6		≤ 150 mm <sup>3</sup>
Length	ISO 10545-2		900mm
Width	ISO 10545-2		595mm
Thickness	ISO 10545-2		20mm
Straightness of Sides	ISO 10545-2		Complies
Squareness	ISO 10545-2		Complies
Surface Flatness	ISO 10545-2		Complies
Linear Thermal Expansion	ISO 10545-8		Complies
Thermal Shock Resistance	ISO 10545-9		Complies
Resistance to Acids (weak)	IOS 10545-13		Complies
Resistance to Acids (strong)	IOS 10545-13		Complies
Resistance to House Hold Cleaning Products	IOS 10545-13		Complies
Resistance to Staining	IOS 10545-14		Min Class 3